



NOTES:
 1. ELECTRICAL:
 1) CURRENT RATING: 2.1A MAX;
 2) VOLTAGE RATING: 18V DC(rms) Max.
 3) INSULATION RESISTANCE: 100MΩ MIN;
 4) CONTACT RESISTANCE: 100mΩ MAX;
 5) OPERATING TEMPERATURE: -25°C TO +80°C.
 2. NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.
 IPNM-082N-9WSU05-P084
 1: Au 1U"
 2: Au 3U"
 6: Au 30U"
 W: WHITE
 B: BLACK
 1: PBT
 2: PA6T
 3: PA9T
 4: LCP
 9: ABS

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	MAT'L	FINISH	Q'TY	TITLE:	PART NO.:	DR:	CHKD:	APPD:	SCALE	SHEET	REV.	CUSTOMER DRAWING
3	MOLDING	LCP OR ABS	1	UL94V-0	X. ±0.35	X.* ±2'	SEE NOTE	SEE NOTE	雅安科技有限公司 ACCURATE INNOTECH INC. iPhone M 8压铸一体式 方头 PCB长14.88 耐高压 gan 2018/05/01 gan 2018/05/01	IPNM-082N-9WSU05-P084	AII-SU05-P084	SCALE: 1:1	SHEET: 1/1	REV: A	CUSTOMER DRAWING		
2	SHELL	ZINC ALLOY	1	PLATED NICKEL	.X ±0.3	.X.* ±1'	SEE NOTE										
1	TERMINAL	COPPER ALLOY	8	PLATED GOLD	.XX ±0.25	.XX*	SEE NOTE										
					.XXX ±0.15	.XXX*	SEE NOTE										
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.																	