





RoHS  
Compliant  
2002/95/EC

Halogen Free

REV.	ECN. NO.	APPD.



RECOMMENDED PCB LAYOUT



NOTES:


- ELECTRICAL:
  - VOLTAGE CURRENT RATING: PIN1&5 1.8AMP MAX / PIN2&3&4 1AMP MAX. ,30V AC;
  - INSULATION RESISTANCE: 100MΩ MIN;
  - CONTACT RESISTANCE: 30mΩ MAX;
  - WITHSTANDING VOLTAGE: 100V AC; FOR 1 MIN.
  - OPERATING TEMPERATURE: -30°C TO +80°C.
- Mechanical:
  - Mating Force: 35N MAX
  - Unmating Force: 10N MIN.
- DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.  
MUYF-051T-4BHUA259  
1:Au 1U\*  
6:Au 30U\*  
T:TIN  
N:NICKEL  
W:WHITE  
B:BLACK  
1:PBT  
2:PA6T  
3:PA9T  
4:LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm	TITLE:	PART NO.:
3	SHELL	COPPER ALLOY / STAINLESS STEEL	1	PLATED TIN	.X	±0.15	MICRO USB B TYPE F 5P SMT沉板式	MUYF-05XT-4BHUA259
2	HOUSING	LCP+30%GF	1	UL94V-0	.XX	±0.10	0.72 四脚全插无导位无接地片	AII-HUA259
1	TERMINAL	COPPER ALLOY	5	PLATED GOLD	.XXX	±0.05	DR: Ricky 2022/09/27	SCALE
					Q'TY		CHKD: Ricky 2022/09/27	SHEET
					APPD:		DR: Ricky 2022/09/27	REV.
							APPD:	CUSTOMER DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.



雅安科技有限公司  
ACCURATE INNOTECH INC.

SCALE: 5:1  
SHEET: 1/1  
REV.: A  
CUSTOMER DRAWING