










RoHS
Compliant
2002/95/EC

Halogen Free

REV.	ECN.	NO.	APPD.



RECOMMENDED PCB LAYOUT



NOTES:

1. ELECTRICAL:

- 1) VOLTAGE CURRENT RATING: PIN1&5 1.8AMP MAX / PIN2&3&4 1AMP MAX. ,30V AC;
- 2) INSULATION RESISTANCE: 100MΩ MIN;
- 3) CONTACT RESISTANCE: 30mΩ MAX;
- 4) WITHSTANDING VOLTAGE: 100V AC; FOR 1 MIN.
- 5) OPERATING TEMPERATURE: -30°C TO +80°C.

2. Mechanical:

- 1) Mating Force: 35N MAX
- 2) Unmating Force: 10N MIN.

3. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.

MUYF-051T-4BHUA324

1:Au 1U*
6:Au 30U*

T:TIN
N:NICKEL

W:WHITE
B:BLACK

1:PBT
2:PA6T
3:PA9T
4:LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm	雅安科技有限公司 ACCURATE INNOTECH INC.							
3	SHELL	STAINLESS STEEL	1	PLATED TIN	.X	±0.15	.X*	±1*	MAT'L	TITLE:	PART NO.:			
2	HOUSING	LCP+30%GF	1	UL94V-0	.XX	±0.10	.XX*	SEE NOTE	FINISH	MICRO USB B TYPE F 5P 牛角型全插	MUYF-05XT-4BHUA324			
1	TERMINAL	COPPER ALLOY	5	PLATED GOLD	.XXX	±0.05	.XXX*	SEE NOTE	Q'TY	DR: Ricky 2022/09/28	DWG NO.:			
					THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.				CHKD: Ricky 2022/09/28		AII-HUA324			
									APPD:		SCALE	SHEET	REV.	CUSTOMER DRAWING
											5:1	1/1	A	