










RoHS  
Compliant  
2002/95/EC

REV.	ECN.	NO.	APPD.



NOTES:

1. ELECTRICAL:

- 1) VOLTAGE CURRENT RATING: 2AMP,30V AC;
- 2) INSULATION RESISTANCE: 1000MΩ MIN;
- 3) CONTACT RESISTANCE: 30mΩ MAX;
- 4) WITHSTANDING VOLTAGE: 500V AC;
- 5) OPERATING TEMPERATURE: -55° C TO +85° C.

2. Mechanical:

- 1) Mating Force: 35N MAX
- 2) Unmating Force: 10N MIN.

3. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

USAF-04\*N-1\*R603

- 1:Au 1U'
- 6:Au 30U'
- W:WHITE
- B:BLACK
- 1:PBT
- 2:PA6T
- 3:PA9T
- 4:LCP

Bill of materials:

3	HOUSING	PBT	1	UL94V-0
2	SHELL	COPPER ALLOY	1	PLATED NICKEL
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN
NO	PARTS	MATERIAL	QTY	FINISHING

TOLERANCES	ANGLES	UNITS
.X ±0.30	±3°	mm
.XX ±0.20		MAT'L
.XXX ±0.10		SEE NOTE
FINISH		
SEE NOTE		
Q'TY		

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC

雅安科技有限公司  
ACCURATE INNOTECH INC.

TITLE:	PART NO.:
USB AF 90度 DIP T型無後蓋直腳	USAF-04*N-1*R603
DR: Ricky 2021/05/19	DWG NO.:
CHKD: Ricky 2021/05/19	AII-R603
APPD:	SCALE SHEET REV. CUSTOMER DRAWING
	1:1 1/1 B