





RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



- NOTES:
- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 2AMP, 30V AC;
 - INSULATION RESISTANCE: 1000M Ω MIN;
 - CONTACT RESISTANCE: 30m Ω MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
 - Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
 - DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.
USAF-04*N-4*V605

1:Au 1U*
6:Au 30U*

W:WHITE
B:BLACK

1:PB
2:PA6T
3:PA9T
4:LC

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	X. ± 0.35	X.* $\pm 2^*$	UNITS	雅安科技有限公司 ACCURATE INNOTECH INC.					
					.X ± 0.3	.X.* $\pm 1^*$	mm	TITLE:	PART NO.:				
3	HOUSING	LCP+30%GF	1	UL94V-0	.XX ± 0.25	.XX*	MAT'L	SEE NOTE	USB AF 沉板2E SMT 四只脚	USAF-04*N-4*V605			
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.XXX ± 0.15	.XXX*	FINISH	SEE NOTE	DR: gan 2014/12/10	DWG NO.: AII-V605			
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.			Q'TY	CHKD: gan 2014/12/10	SCALE	SHEET	REV.	CUSTOMER
									APPD:	1:1	1/1	B	DRAWING