



RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.









A

B

C

D

E



NOTES:

- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 2AMP, 30VAC;
 - INSULATION RESISTANCE: 1000MΩ MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
- Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
- NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.

USAF-08*N-1*P62

1: Au 1U"
6: Au 30U"

W: WHITE
B: BLACK
1: PBT
2: PA6T
3: PA9T
4: LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	X. ±0.35	X.' ±2°	UNITS	雅安科技有限公司 ACCURATE INNOTECH INC.				
4	CLIP	COPPER ALLOY	1	PLATED NICKEL	.X ±0.3	.X' ±1°	mm	TITLE: USB A F DIP 180° 双层短体		PART NO.: USAF-08*N-1*P62		
3	HOUSING	PBT	1	UL94V-0	.XX ±0.25	.XX'	MAT'L	DR: gan 2012/6/30		DWG NO.: AII-P62		
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.XXX ±0.15	.XXX'	SEE NOTE	CHKD: gan 2012/6/30		SCALE: 1:1		
1	TERMINAL	COPPER ALLOY	8	PLATED GOLD/TIN	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.		FINISH	APPD:		SHEET: 1/1	REV.: B	CUSTOMER DRAWING
							Q'TY					

1

2

3

4

5

6

7