








RoHS Compliant
2002/95/EC
Halogen Free

REV	LTR	DESCRIPTION	DATE	REVISER	APPD



PIN NUMBER	SIGNAL NAME
1	VBUS
2	D-
3	D+
4	GND
5	SSRX-
6	SSRX+
7	GND
8	SSTX-
9	SSTX+
Shell	Shield



NOTES:

- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 1.8AMP, 30V AC;
 - INSULATION RESISTANCE: 100MΩ MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 100V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
- Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
- NOTE: DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.


4. PART NO.

USAF-09*N-4BLCC14
 1:Au 1U"
 5:Au 15U"
 6:Au 30U"
 W:WHITE
 B:BLACK
 BL:BLUE
 1:PB
 2:PA6T
 3:PA9T
 4:LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	X.	X.' ±2'	UNITS	mm	雅安科技有限公司 ACCURATE INNOTECH INC.			
4	SHELL	STAINLESS STEEL	1	PLATED NICKEL	X. ±0.35	X.' ±2'	MAT'L	mm	TITLE: USB 3.0 AF 90度 侧插式 外壳无卷边 小鱼叉脚 成品图 PART NO.: USAF-09*N-4BLCC14 DR: gan 2017/1/14 DWG NO.: AII-CC14 CHKD: gan 2017/1/14 APPD:			
3	HOUSING	LCP/PBT+30%GF	1	UL94V-0	.X ±0.3	.X' ±1'	SEE NOTE	SEE NOTE				
2	TERMINAL2	COPPER ALLOY	4	PLATED GOLD/TIN	.XX ±0.25	.XX'	FINISH	SEE NOTE				
1	TERMINAL1	COPPER ALLOY	5	PLATED GOLD/TIN	.XXX ±0.15	.XXX'	Q'TY	SEE NOTE				
NO	PARTS	MATERIAL	QTY	FINISHING								

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.



SCALE: 1:1
 SHEET: 1/1
 REV.: B
 CUSTOMER DRAWING